


T-1-3/4, Right-Angle LED Assembly G63XB Series (Snap-together Style)



The G63XB series of right-angle indicators is made from interlocking units. This series is available with leads cut to 4 mm as standard. In addition to the variety of lamps listed below, most T-1-3/4 LEDs, from blue to super bright red, can be special ordered.



Specify part desired as follows:

G63NB/Order Code1 + ... + Order Code N; Where N = number of segments.

For example: "G634B/1+3G" designates an assembly with 1 red LED on the left and 3 green LEDs to the right.

It is recommended that N ≤ 8 to minimize handling difficulty and tolerance build up.



RoHS Compliant
Aug 2004

ORDER CODE AND INFORMATION (ALL RATINGS AT 25°C AMBIENT)

LED Lamp			Typical Characteristics				Recom. Op. If (mA)
Epoxy & Type	Color	Order Code	Peak λ (nm)	Vf (V) @If=20mA	Iv (mcd) @If=10mA	2Θ _{1/2} (Deg)	
Tinted Diffused Resistor Required	Red	H	697	2.1	2.0	36	5-10
	Hi Eff Red	I	635	2.0	9.0	36	10-20
	Green	G	565	2.1	9.0	36	10-20
	Yellow	Y	585	2.0	7.0	36	10-20
Tinted Transparent High Brightness	Hi Eff Red	IT	635	2.0	30	16	10-20
	Green	GT	565	2.1	30	16	10-20
	Yellow	YT	585	2.0	28	16	10-20
Tinted Diffused For 2mA Operation	Red	H2	697	2.0	1.6 @ 2mA	36	2-10
	Hi Eff Red	I2	635	2.1	2.0 @ 2mA	36	2-10
	Green	G2	565	2.0	2.0 @ 2mA	36	2-10
	Yellow	Y2	585	2.0	2.0 @ 2mA	36	2-10
Tinted Diffused 5V Operation	Not available in this series.						
Tinted Diffused 12V Operation							
White Diffused Bipolar, Bicolor	Hi Eff Red/Grn	EG	635/565	2.1/2.0	2.5/2.5	54	10-20
	Yellow/Green	YG	585/565	2.1/2.0	2.5/2.5	54	10-20
	Red/Green	SG	660/570	1.8/2.2	6.0/2.5	-	10-20

* Specifications subject to change without notice. Dimensions are in mm±0.25 unless stated otherwise.